



- professional mask with unique design
- High performance bearing capacity
- 0.016 second interactive speed
- High precision and seamless design
- Interestin interactive materical

LED Floor screen

Model	P2.976	P3.91	P4.81	P6.25
Usage	Indoor/outdoor	Indoor/outdoor	Indoor/outdoor	Indoor/outdoor
Cabinet size(mm)	500x500/500x1000	500x500/500x1000	500x500/500x1000	500x500/500x1000
Cabinet resolution (dot)	168X168/168X336	128X128/128X256	104X104/104X208	30X60/60X60
Scanning	1/28S	1/32S 1/16S	1/26S 1/13S	1/10S
LED type	SMD1921	SMD1921	SMD1921	SMD1921/2727
Interactive way	Build-in chip / radar	Build-in chip / radar	Build-in chip / radar	Build-in chip / radar
Installation	Front/Back	Front/Back	Front/Back	Front/Back
Density(dot/m ²)	112896	65536	43264	25600
Brightness(cd/m ²)	1800/5000	1800/4000	1800/4000	1800/4000
Max. Power Consumption	800	800	800	800
Average Power Consumption	400	400	400	400
Cabinet weight (kg)	11.5/12.5KG	11.5/12.5KG	11.5/12.5KG	11.5/12.5KG
Cabinet material	Iron/aluminum	Iron/aluminum	Iron/aluminum	Iron/aluminum
IP rate	IP 68	IP 68	IP 68	IP 68
Grayscale	10000:1	10000:1	10000:1	10000:1
Refresh rate(hz)	1920-3840	1920-3840	1920-3840	1920-3840
Frame change frequency	50/60hz	50/60hz	50/60hz	50/60hz
Horizontal viewing angle	>120°	>120°	>120°	>120°
Vertical viewing angle	>120°	>120°	>120°	>120°
Input Voltage	AC110V - AC220V	AC110V - AC220V	AC110V - AC220V	AC110V - AC220V
Temperature-operating	- 10℃ ~ 60℃	- 10℃ ~ 60℃	- 10℃ ~ 60℃	- 10℃ ~ 60℃
Humidity-operating	10% ~ 90%	10% ~ 90%	10% ~ 90%	10% ~ 90%
Life span (H)	≥100,000	≥100,000	≥100,000	≥100,000
MTBF (H)	>10,000	>10,000	>10,000	>10,000

Cabinet show



Project Case

