

Virtual Production LED Wall

Key Features

- Background switching at wills
- Can integrate multiple functions
- Immersive 270-degree coverage
- Configure various parameters to suit scene



Update content in real-time



Create an immersive experience



Make a memorable impact

Get more information & quotes

Web: www.szjy-led.com

Email: sale20@sz-ledscreen.com

Mobile: +86 18194008750

Specification

Custom Your Virtual Production LED Wall !



Recommended Models			
Model	P1.25	P1.538	P1.86
Module size(mm)	320x160	208x104	320x160
Module resolution (dot)	64x32	32x32	172x86
Scanning	1/64S	1/52S	1/43S
SMD	1G1R1B		
Maintenance	Front		
Installation	Front/Back	Front/Back	Back
Cabinet size(mm)	Customized		
Density(dot/m ²)	640000	422500	288369
Brightness(cd/m ²)	600-1000		
Max. Power Consumption(W)	600		
Average Power Consumption(W)	200		
Cabinet weight (kg)	18kg/m ²		
Cabinet material	Iron		
IP rate	IP 31		
Grayscale	10000:1		
Refresh rate(hz)	1920-3840		
Frame change frequency	50/60hz		
Horizontal viewing angle	> 140°		
Vertical viewing angle	> 140°		
Best viewing distance	> 1.2m	> 1.5m	> 1.8m
Input Voltage	AC110V - AC220V		
Module Max. current	4.0-5.0		
Temperature-operating	- 10°C ~ 60°C		
Humidity-operating	10% ~ 90%		
Life span (H)	≥100,000		

Get more information & quotes

Web: www.szjy-led.com

Email: sale20@sz-ledscreen.com

Mobile: +86 18194008750

Virtual Production LED Wall

Product Cases



Film Shooting and Production



XR Stages and Exhibitions



Improves Your Productivity

Get more information & quotes

Web: www.szjy-led.com

Email: sale20@sz-ledscreen.com

Mobile: +86 18194008750