

Waterproof LED Screen

Key Features

- Ultra-clear Display
- Up to 5500cd/m² brightness
- IP68 rating waterproof protection
- Powerful heat dissipation performance



Outdoor Advertising



Tourism Promotion



Broadcast Live Match

Get more information & quotes

Web: www.szjy-led.com

Email: sale20@sz-ledscreen.com

Mobile: +86 18194008750

Specification

Custom Your Waterproof LED Screen !



Recommended Models			
Model	P5	P6	P8
Module size(mm)	320x160	192x192	320x160
Module resolution (dot)	64x32	32x32	40x20
Scanning	1/8S	1/8S	1/5S
SMD	1G1R1B		
Maintenance	Front/Back	Front/Back	Back
Installation	Front/Back	Front/Back	Back
Cabinet size(mm)	960*960		
Density(dot/m ²)	40000	27777	15625
Brightness(cd/m ²)	5000-5500	5000-5500	5000-5500
Max. Power Consumption(W)	1000	1000	1000
Average Power Consumption(W)	350	350	350
Cabinet weight (kg)	40kg/m ²		
Cabinet material	Iron		
IP rate	IP 68		
Grayscale	10000:1		
Refresh rate(hz)	1920-3840		
Frame change frequency	50/60hz		
Horizontal viewing angle	> 140°		
Vertical viewing angle	> 140°		
Best viewing distance	> 5m	> 6m	> 8m
Input Voltage	AC110V - AC220V		
Module Max. current	5.5-7.5	3.5-5.5	5.5-7.0
Temperature-operating	- 10°C ~ 60°C		
Humidity-operating	10% ~ 90%		
Life span (H)	≥100,000		

Get more information & quotes

Web: www.szjy-led.com

Email: sale20@sz-ledscreen.com

Mobile: +86 18194008750

Waterproof LED Screen

Product Cases



Single Post Installation



Wall-mounted Installation



Back Support Installation

Get more information & quotes

Web: www.szjy-led.com

Email: sale20@sz-ledscreen.com

Mobile: +86 18194008750